MFC-9335CDW





Colour LED Multi-Function Centre® with Networking Capability (Print / Scan / Copy / Fax)

The MFC-9335CDW is the high speed all-in-one, offering wireless connectivity and 2-sided printing to suit your busy office.

- Print / Copy / Scan / Fax
- Fast Printing Up to 22ppm colour and monochrome printing
- Save Money Automatic 2-sided (duplex) Printing
- Convenience Print without PC using mobile print
- Easy Sharing Connect with multiple users via wired/wireless network
- Reduce Running Costs Choice of high-yield colour toners for heavy print volume

For increased productivity, the MFC-9335CDW offers fast and efficient colour and monochrome print speeds of up to 22 pages per minute and multi-functions - print, scan, copy and fax.

With automatic 2 - sided printing, you can print on both sides and save on costs. Share your printer easily with other users by connecting it via the wireless network. With the mobile print capability, you can print your documents from your mobile without the use of a PC. Navigate easily with the intuitive 9.3cm colour Touch Screen display and improve your productivity in the office.

Brother's high-yield toner cartridges will enable you to enjoy a lower cost per page for large print volumes. For greater efficiency and more cost savings, Brother is the perfect choice.

General

Technology

Memory Local Interface

Wired Network Interface Wireless Network Interface Display Mobile Connectivity

Easy Wireless Setup

Electrophotographic LED Printer

333winz 192MB Hi-Speed USB 2.0 & USB Host for direct print and scan from a USB Flash Drive, Near Field Communication(NFC) Ethernet (10Base-T/100Base-TX)

IEEE 802.11b/g/n 9.3cm TFT colour touchscreen

9.3cm IFI Colour buchscreen

Brother iPrint&Scan app, AirPrint, Google Cloud Print™ & Wi-Fi Direct™,NFC

Web Connect Print from and scan to DropBox, Evernote®, Facebook,

Flickr®, Google Drive™, Picasa™ & SkyDrive®

Wi-Fi Protected Setup™ (WPS) & AirStation

OneTouch Secure System™ (AOSS)



Automatic 2-Sided Colour Printer

Print Speed (A4) 2-Sided Print Speed (A4) Resolution Print Languages FPOT (First Print Out Time) Warm Up Time

Up to 22ppm (pages per minute) colour & mono Up to 7ipm (images per minute) colour & mono Up to 7ipm (images per minute) colour & mono 2,400dpi (2,400 x 600dpi), 600 x 600dpi PCL6, BR-Script3 (PostScript3°0 x Language Emulation) Less than 16 seconds colour & mono from ready mode Less than 24 seconds from sleep mode

Colour Fax

Modem Speed Dials 33.6kbps Super G3

200 locations for pre-stored numbers

Page Memory Up to 500 pages (ITU-T Test Chart, Standard Resolution, JBIG) Fax forwarding, remote access, fax retrieval, dual access, I-Fax³, PC-Fax send, PC-Fax receive⁴, auto reduction, group dials, error correction mode & Other Functions distinctive ring

Colour Copier

Resolution Multi copy Up to 22cpm (copies per minute) colour & mono

600 x 600dpi

Makes up to 99 copies of each page (stacks or sorts)

Enlargement / Reduction Ratio Reduce & enlarge documents from 25% to 400% using 1% increments

Colour Scanner

Resolution

Up to 1,200 x 2,400dpi (from flatbed), 1,200 x 600dpi (from ADF),

19,200 x 19,200dpi (interpolated) 256 shades of grey Grey Scale

Colour Depth 48bit internal / 24bit external colour scanner Pull Scan Functions Scan to email, OCR, image, file & searchable PDF (requires bundled software)

Push Scan Functions Scan to network folder⁵, FTP & email server³

TWAIN, WIA, ICA, SANE³ Drivers

Paper Handling

Paper Input

Media Type

250 sheet standard paper tray sheet manual feed slot

35 sheet automatic document feeder (ADF)

100 sheets face down, 1 sheet face up (straight paper path) Paper Output

Standard Tray - Plain & recycled paper (60 - 105gsm)

Manual Feed Slot - Plain, recycled, glossy & bond paper (60 - 163gsm)

ADF - Plain & recycled paper (64 - 90gsm)

Media size

Standard Tray - A4, Letter, B5 (JIS), A5, A5 (Long Edge), A6, Executive, Legal, Folio (A4 only supported in automatic 2-sided print mode) Manual Feed Slot - Width: 76.2 to 215.9mm x Length: 116 to 355.6mm ADF - Width: 147.3mm to 215.9mm x Length 147.3mm to 355.6mm Yes, from manual feed slot (accuracy & reliability will depend on the quality &

Envelope & Label Printing

type of media used)

Supported Operating Systems

Windows

Windows 10® (32 & 64 bit editions), Windows 8®/8.1 (32 & 64 bit editions),

Windows 7[®] (32 & 64 bit editions), Windows Vista[®] (32 & 64 bit editions),

Windows® XP Professional (32 & 64 bit editions), Windows® XP Home Edition, Windows® Server 2012, Windows® Server 2008 R2.

Windows® Server 2008 (32 & 64 bit editions), Windows® Server 2003 (32 & 64 bit editions). Windows® Server supports printing only

Mac OS X 10.6.8 or greater CUPS, LPD/LPRng (x86/x64 environment) Macintosh Linux

Printer Driver Functions

N-up Printing4 Poster Printing Watermark Printing⁵ ID Printing⁵ Booklet Printing⁴ Skip Blank Page

Print Text in Black⁴

Reduce up to 2, 4, 9, 16 or 25 A4 pages into just one A4 page Enlarge 1 A4 page into a poster using 4, 9, 16 or 25 A4 pages Add predefined text to your documents as a watermark Add identification to your printed documents

Print documents in A5 booklet format Ignores any blank pages in your documents Converts all text in your documents to black when printed

Supplies

Inbox Toners Standard Toners

High Yield Colour Toners Waste Toner Box

1,000 pages¹ TN-251BK - 2,500 pages¹ TN-251C/M/Y - 1,400 pages¹ TN-255C/M/Y - 2,200 pages¹ DR-251CL - 15,000 A4 pages BU-220CL - Up to 50,000 pages WT-220CL - Up to 50,000 pages



Weights & Dimensions

Without Carton

410(W) x 483(D) x 410(H) mm 18.5kg

Environment

TEC Value

Toner Save

1.4kWh / week

375W active, 70W ready, 7.5W sleep, 0.05W deep sleep

Sound Pressure 53dBA active, 33dBA ready 6.42B active, 4.44B ready Sound Powe Power Save

Consume less energy when not in use

Reduces toner usage

Duty Cycle

Recommended Monthly Print Volume

300 to 1,500 pages



Approx. declared yield value in accordance with ISO/IEC19798 *Vertical x horizontal *Optional free download from the Brother Solutions Centre http://support.brother.com 4Windows and Mac. 9Windows Only

Contact:







