



Rugged mobile printing

whatever the conditions

RJ-4230B



Our RJ-4230B mobile printer is fast, compact and extremely rugged. It empowers workers to operate in any environment with speed, accuracy and efficiency.

It has built-in Bluetooth connectivity, printing up to 4" width receipts, quotes, tickets, invoices and labels on demand.



Reliable Connectivity

Provides multiple connectivity options for use in different environments, with USB and Bluetooth (low energy) with MFI capabilities and passive NFC.



Robust Design

The RJ-4230B is our toughest yet, with an IP54 rating and drop tested up to 2.1 metres, providing the ultimate in durability.



Easy to deploy

Using the new Mobile Deploy App, update your printer remotely from any location. For more information, visit brother.com.au/service-and-support/labelling-apps.html



Easy to use

The LCD screen with menu options makes it easy to program as well as a backlight that ensures you can see it in dark conditions.



Seamless Integration

Printer drivers are available for Windows OS and software development kits can be downloaded to support Android and iOS operating systems.



Customisation

We have a wide range of accessories made to suit any environment. See next page.



Brother Font Manager

Brother Font Manager can be used to convert and download fonts in characters or languages not supported by built-in fonts. These can then be stored on a RJ printer and recalled later when printing receipts and labels. For more information, visit brother.com.au/service-and-support/labelling-apps.html





Warehouse

Shelf edge Labels Shipping Labels Delivery Reports

Ideal for these markets

Designed to meet the needs of specialist business sectors




Logistics & Deliveries

Delivery Report Inventory Report Invoicing




Ticketing

Parking Notice Parking Fine



Field Sales

Contract
Quotation
Receipt
Product Documentation



Field Service

Invoice Receipt Service Documentation Contract

Customise your solution

Brother has designed and engineered a wide range of accessories to meet your specific requirement with a customised solution and are available to enhance your workflow for both in-vehicle and on-body applications.

Power options & accessories



PA-BT-006Rechargeable Li-ion smart battery



PA-AD-600 AC adapter



PA-CD-600WRPermanently wired



PA-CD-600CGCigar lighter plug



PA-CR-002Single charging cradle



PA-BC-003
Single battery charger
(Up to 4 can be daisy chained together and run off of a single power point)



PA-SS-4000 Shoulder strap



Media options

RD-M03C1

Die cut label (102mm x 152mm) 3PK

RD-M01C5

Continuous roll (102mm) 3PK

RD-M13C5

Continuous roll (80mm) 3PK

RJ-4230B Series - Specifications and Features

Printing / Media	
Printing technology	Direct thermal
Print resolution	203dpi
Print speed*	Maximum 127mm/second (5ips)
Maximum print width	104mm
Maximum print length	3000mm
Number of labels per battery charge	Li-ion battery: approx. 10,000 labels (continuous print)*
Fear bar	Double
Vedia width	45-113mm
Media types	Receipts, Labels, Tags and Linerless
Roll diameter	58mm max
LCD	
Гуре	Monochrome LCD with backlight
Connectivity	Monodinomo 200 With Saokinght
JSB	USB version 2.0 (mini-B type)
Bluetooth	Bluetooth Version 4.2 (Low-energy support)
	SPP (Serial Port Profile)
Bluetooth profiles	OPP (Object Push Profile)
	HCRP (Hard Copy Cable Replacment Profile)
	iAP supported
MFi support	Yes
NFC	Yes (Passive)
General	
Operating system support	Microsoft® Windows® 7 / Windows® 8 / Windows® 8.1 / Windows® 10
SDK availability	Brother Print SDK for Android™
	(for Android 4.0.3 or later)
	Brother Print SDK for iPhone/iPad (for iOS 7 or later)
Supported printer commands	P-touch template
	ZPLII emulation
	CPCL emulation
	ESC/P Raster
_abel Editing Software	BarTender Ultra Lite Edition ¹
Memory	But foliation of the Edition
RAM	256MB
Flash	64MB
Environmental	OTIVID
Orop protection*	2.1 metres
Sealing	IP54
	Operating: -20°C to +55°C / Charging: 0°C to +40°C
Operating temperature	-20°C to 60°C
Storage temperature	-20 0 10 00 0
Power	Dechargeable Lities Const Detter (DA DT 000) 7.0
Battery (optional accessory)	Rechargeable Li-ion Smart Battery (PA-BT-006), 7.2v
AC adapter (optional accessory)	110/220V AC (50/60Hz) to 15V DC
Car adapter (optional accessory)	12V DC
Weights / Dimensions	
Dimensions	153(w) x 68(h) x 159(d) mm 850g
Weight (with battery)	

Box Contents

Printer
Belt clip
Adjuster guide locks
Documentation









linkedin.com/company/brother-international-australia/