



## **TD-4420D Series**

203dpi Direct Thermal Printers

TD-4420DN TD-4420DNP TD-4420DNC



Healthcare, medical and laboratory



Warehousing and logistics



Retail

www.brother.com.au

# Direct Thermal Desktop Printers

4-inch 203dpi Barcode Label and Receipt Printers

TD-4420DN TD-4420DNP TD-4420DNC



Introducing the next era of four-inch desktop thermal printers from Brother. These precision built barcode label and receipt printers, deliver performance, quality, and integration at an exceptional value. From inventory and shipping to barcode and shelf labelling – now you can easily and affordably produce the labels you need, with the reliability and support that only Brother delivers.



#### **Effortless integration**

Experience improved operational efficiency with seamless integration into existing and future workflows utilising b-PAC, Software Development Kits (SDKs), PDF Crop tool, BarTender and the support of a variety of printer command systems, including ZPLII, EPL/DPL emulation



#### Warranty

Delivering peace of mind with a 2 year return to base warranty on hardware and a 6 month return to base warranty on print heads. Rapid exchange is also available as an optional add-on



#### Reliable technology

Thermal technology is made up of less moving parts delivering greater reliability for vour business



#### A full thermal print solution

Design and print from start to finish with Brother's free P-touch Editor label design software. With hundreds of templates and barcode creation, label development for any industry can be achieved

### **Technical Specifications for the TD-4420D Series**

	TD-4420DN	TD-4420DNP	TD-4420DNC		
Tear Bar	Yes	N/A	N/A		
Peeler (PA-LP-001)	No (available as an option)	Yes (installed)	No		
Cutter (PA-CU-001)	No (available as an option)	No	Yes (installed)		
	Pri	Printing			
Print Technology		Direct Thermal			
Print Resolution	203 dpi				
Print Speed	MAX up to 203.2mm/sec (8 ips) (Under Brother standard environment)				
Print Width (MAX)	108.4mm (4.27 inch)				
Print Length (MAX)	3,000mm (118.11 inch)				
Media Sensor Type	Gap (Transmissive), Black mark (Reflective)				
Media Sensor Location	Reflective (adjustable), Gap (fixed)				
Release Mode	Standard: Continuous, tear off	Peeler	Cutter		
	Size				
Weight	Printer: 2.08kg	Printer & Peeler: 2.20kg	Printer & Cutter: 2.45kg		
Dimensions	180mm (W) (7.08 inch) 155mm (H) (6.10 inch) 224mm (D) (8.82 inch)	180mm (W) (7.08 inch) 155mm (H) (6.10 inch) 259mm (D) (10.20 inch)	180mm (W) (7.08 inch) 155mm (H) (6.10 inch) 267mm (D) (10.51 inch)		
Control Panel	3 LED 3 button (Power/ Feed/ Print)				
	Interface				
USB	Yes: USB Ver.2.0 (Full Speed) (Type B)				
Serial	Yes: RS232C (DB9 male)				
Wired LAN	10/100BASE-TX				
Bluetooth	Not supported				
WLAN	Not supported				
	Memory				
RAM	256MB				
Flash	64MB (User area 40MB)				
	Power Supply				
Adapter	AC adapter (100 - 240 V 50/60Hz)				
	Media Specification				
Types	Wristbands, Continuous, Die Cut, Fan Fold, Perforated, Tag				
Wound Type	Outside wound				
Media Width	19 ~ 118mm (0.75 inch to 4.65 inch) catalogue described spec				
Media Length	6.4mm ~ Max. print length (0.25 inch to Max inch)   Tear mode: 18mm ~ Max. print length Peeler mode: 17 ~ Max. print length   Cutter mode: 20mm ~ Max. print length				
Thickness	0.06 ~ 0.279mm				
Diameter (Max)	127mm				
Core Diameter (Min)		12.7mm			

		tware		
Label Editing Software	P-touch Ed	itor ver. 5.2 and supports BarTender Lite a	as optional	
Windows Printer Driver	Microsoft Windows10 (x86,x64), Micro	Microsoft Windows7 (x86/x64), Microsoft Windoes8 (x86/x64), Microsoft Windows 8.1 (x86,x64), oft Windows10 (x86,x64), Microsoft Windows Server 2008 R2 (x64), Microsoft Windows Server 2012 (x64)/Server 2012R2 (x64)/Microsoft Windows Server 2016		
Linux Printer Driver		Ubuntu V11.04-16.04 Fedora 24 SUSE Linux Enterprise Server 12 CentOS Linux 7.2 Red Hat Enterprise 7.3		
MacOS Printer Driver		MacOS 10.5.2 or greater using the built-in ZPL driver.  Please click <u>here</u> to contact us prior to purchase for setup instructions)		
Setting Tool		BPM (Brother Printer Management Tool) Support OS Windows 7 Windows 8, 8.1 Windows 10		
Mobile SDK	Android 4.0.3 or later, iOS 8 or later			
Mobile Transfer Express Mobile Deploy	Not supported			
Windows SDK	Windows 10 and Server 2016, Windows 8.1 and Server 2012 R2, Windows 8 and Server 2012, Windows 7 and Server 2008 R2, Windows Server 2008			
Supported Command	Raster, ESC/P, P-touch Template, ZPLII, EPL, DPL, CPCL (CPCL page print mode / CPCL line print mode)			
SAP Device Type	SAP_BASIS Release 6.20~7.11, except 7.10.			
Development Support Tool		CommTool (Brother Communication Tool)		
Bar Code Symbologies	Linear:  Code128UCC, Code128 subsets ABC, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code39, Code39 with check digit, Code93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, Code11, TELEPEN, TELEPENN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS  2-dimensional:  GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417			
Fonts	8 alpha-numeric bitmap fonts for FBPL  Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font			
Add-in for Microsoft	Microsoft Word 2007 (x86), Microsoft Word 2010 (x86), Microsoft Word 2013 (x86), Microsoft Word 2016 (x86), Microsoft Excel 2007 (x86), Microsoft Excel 2010 (x86), Microsoft Excel 2013 (x86), Microsoft Excel 2016 (x86), Microsoft Outlook 2007 (x86), Microsoft Outlook 2010 (x86), Microsoft Outlook 2013 (x86), Microsoft Outlook 2016 (x86)			
Database File Compatibility	csv, txt, mdb, xls, accdb xlsx xlsm, Microsoft SQL Server Database, accdb, xlsx, xlsm			
	Operating C	haracteristics		
Operating Temperature	Operate: 5 ~ 40°C			
Operating Humidity	25 ~ 85% non-condensing			
Storage Temperature	40 ~ 60 °C			
Storage Humidity	10 ~ 90% non-condensing			
Printer Safety	EMC / RMC			
	Wai	ranty		
Hardware	2 Year Return to Base			
Print Head	6 Month or 30kms Return to Base (whichever is first)			
Options	Rapid Exchange - contact Brother at info@brother.com.au for more information			
	Package Contents			
Package Contents	Printer, AC Adapter, Power Cord, USB Cable, Documents	Printer, Label Peeler, AC Adapter, Power Cord, USB Cable, Documents	Printer, Cutter, AC Adapter, Power Cord, USB Cable, Documents	



#### Working with you for a better environment

At Brother, our green initiative is simple. We strive to take responsibility, act respectfully and try to make a positive difference to help build a society where sustainable development can be achieved. We call this approach Brother Earth.







/brotheraustralia



All specifications correct at the time of printing and are subject to change. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies.